

CUB-XZ1127
9 FEB'2017



Special Price:
R54,150
1 Week only!



Zero-Turn Lawn Tractor

107 cm/42" Side Discharge

SIDE DISCHARGE

Nett Price:
R64,980
INCL. VAT
Please note this price is only valid from Head Office, contact Branches for price with courier cost in your area.

Make yourself comfortable as you mow your way to a pristine lawn. Smooth, responsive zero-turn handling delivers incredible precision and efficiency. A reinforced steel frame and chassis with a heavy-duty fabricated front axle, the RZT42 is above all else, strong. Combined with its ball-bearing hubs, you can tackle the toughest of terrain without feeling it. That's high performance and durability working together in a perfect union. A wide operator station, dual-adjustment lap bars and a high-back Cub Comfort™ seat make for the most spacious, comfortable zero-turn experience. An advanced cutting system design with optimal airflow, blade overlap and floating deck deliver flawless cutting and bagging performance

- Cutting Height Range:** 38mm-100mm
- Cylinders:** Single
- Displacement:** 547cc
- Engine:** Cub Cadet OHV
- Power:** 12.5 kW / 2,300 rpm
- Transmission:** Dual Hydrostatic

NOTE: Specifications may vary according to the types, and are subject to change without notice.



HEAD OFFICE: NIGEL, GAUTENG
Cnr. Third Ave & Klippen Road, Vorsterskroon
Tel: 011 730 3400 / Fax: 011 814 2345
Email: info@turfmaster.co.za
Website: www.turfmaster.co.za

BRANCHES:				
Bellville Cnr Cilmor & Labelle Rd, Stikland, Bellville Tel: (021) 945-4106/7/8 Fax: (021) 946-2371	Durban Cnr Bevis & Bishop Rd No.11 Old Main Road, Pinetown Tel: (031) 701 8233 Fax: (031) 701 3097	Nelspruit Cnr Friedenheim & Fuchsia Rd, Nelspruit Tel: (013) 492 0490	Port Elizabeth 20 – 6th Ave., Walmer, Port Elizabeth Tel: (041) 581-8443/4/5 Fax: (041) 581-8446	Pretoria Unit 9 Miracle Park, Lenchen Ave Ext off Old JHB Road, Centurion Tel: (012) 653-8342/8 Fax: (012) 653-8343
				Roodepoort 9 Sonop Street, Horizon, Tel: 076 921 5469

SPECIFICATIONS

ENGINE	RZT 42
Engine type	Cub Cadet OHV
Engine displacement (cm ³)	547
Rated power (kW/min ⁻¹)	12,5 / 2.300
Cylinders	Single
Tank volume (capacity) (l)	11,4
Lubrication	Oil pump with oil filter

DRIVE SYSTEM

Transmission	Dual Hydrostatic
--------------	------------------

DISCHARGE SYSTEM

Bag	Optional 200 l / 19B70020OEM
Grass deflector	Standard

WHEELS

Wheel size (f/r) (mm)	11" x 4" / 18" x 8,5"
Turning radius (cm)	Zero

ADDITIONAL SPECIFICATIONS

Mowing areas m ² /h	> 2.000
Cutting width (cm)	107
Cutting height (min-max)	38 - 100 mm
Cutting options	3 in 1 Option
Deck engagement	Electro-magnetic
Deck height positions	8
Wash nozzle / mulching plug	Standard / Standard

DIMENSIONS

LpA /LwA/LwAg (dB)	88 / 98 / 100
Vibration value body/ (k-factor)	1 / 0,5 m/s ²
Vibration value hand-arm/ (k-factor)	5 / 1,5 m/s ²
Dimensions (L/W/H) (cm)	203 / 116 / 92
Weight net (kg)	228