

SIDE DISCHARGE

Zero-Turn Lawn Tractor 117 cm/46"



Nett Price:

R62,000

EXCL. VAT

Please note this price is only valid from Head Office, contact Branches for price with courier cost in your area.

The Cub Cadet RZT-S46 has a steering wheel so it's easy to operate and control. The RZT-S46 delivers true zero-turn manoeuvrability with steering wheel control over all four wheels you get unmatched stability on steep and diverse terrain - and anywhere else. The advanced cutting system with optimal airflow, blade overlap and floating deck delivers a consistent, flawless, high-quality cut. The dedicated dual hydrostatic rear-wheel transmission delivers effortless zero-turn control, synchronized with the steering to reduce turf damage which means that you can expect superior performance and an enviable lawn.

Bag Capacity: Accessory 19A70020OEM, 210 litre twin bag

Cutting Height Range: 38mm-100mm

Cylinders: V-Twin

Displacement: 726 cc

Engine: Kawasaki OHV

Power: 14.1 kW / 2,400 rpm

Transmission: Dual Hydrostatic

NOTE: Specifications may vary according to the types, and are subject to change without notice.

TURFMASTER

(PTY) LTD



HEAD OFFICE: NIGEL, GAUTENG

1 Third Avenue, Vorsterkroon

Tel: 011 730 3400 / Fax: 011 814 2345

Email: info@turfmaster.co.za

Website: www.turfmaster.co.za

BRANCHES:

Bellville
Cnr Cilmor & Labelle Rd,
Stikland, Bellville
Tel: (021) 945-4106/7/8
Fax: (021) 946-2371

Durban
Cnr Bevis & Bishop Rd
No.11 Old Main Road, Pinetown
Tel: (031) 701 8233
Fax: (031) 701 3097

Nelspruit
Cnr Friedenheim
& Fuchsia Rd,
Nelspruit
Tel: (013) 492 0490

Port Elizabeth
20 – 6th Ave.,
Walmer, Port Elizabeth
Tel: (041) 581-8443/4/5
Fax: (041) 581-8446

Pretoria
Unit 9 Miracle Park, Lenchen Ave
Ext off Old JHB Road, Centurion
Tel: (012) 653-8342/8
Fax: (012) 653-8343

SPECIFICATIONS

ENGINE	RZT-S 42	RZT-S 46
Engine type Kawasaki OHV	
Engine displacement (cm ³)	603	726
Rated power (kW/min ⁻¹)	10,0 / 2.400	14,1 / 2.400
Cylinders V-Twin	
Tank volume (capacity) (l) 10,5	
Lubrication Oil pump with oil filter	

DRIVE SYSTEM

Transmission Dual Hydrostatic	
--------------	---------------------------------	--

DISCHARGE SYSTEM

Bag Optional 200 l / 19B70020OEM	
Grass deflector Standard	

WHEELS

Wheel size (f/r) (mm) 13" x 5" / 18" x 9,5"	
Turning radius (cm) Zero	

ADDITIONAL SPECIFICATIONS

Mowing areas m ² /h	> 2.000	> 3.000
Cutting width (cm)	107	117
Cutting height (min-max) 38 - 100 mm	
Cutting options 3 in 1 Option	
Deck engagement Electro-magnetic	
Deck height positions 8	
Wash nozzle / mulching plug Standard / Standard	

DIMENSIONS

LpA /LwA/LwAg (dB) 88 / 98 / 100	
Vibration value body/ (k-factor) 1 / 0,5 m/s ²	
Vibration value hand-arm/ (k-factor) 5 / 1,5 m/s ²	
Dimensions (L/W/H) (cm)	203 / 116 / 118	203 / 126 / 118
Weight net (kg)	234	256