

HONDA ENGINES

HONDA GX200 HORIZONTAL ENGINE



Honda's GX series engines are legendary for superior reliability and performance. And there's no doubt about it: the GX200 lives up to the legend. Lower noise levels, lower vibration, and lower emissions – without sacrificing power output or performance.

Engine Type	Air-cooled 4-stroke OHV
Bore x Stroke	68 X 54 mm
Displacement	196 cm3
Net Power Output*	5.5 HP (4.1 kW) @ 3,600 rpm
Net Torque	9.1 lb-ft (12.4 Nm) @ 2,500 rpm
PTO Shaft Rotation	Counter clockwise (from PTO shaft side)
Compression Ratio	8.5:1
Lamp/Charge coil options	25W, 50W / 1A, 3A, 7A
Carburetor	Butterfly
Ignition System	Transistorized magneto
Starting System	Recoil Starter
Lubrication System	Splash
Governor System	Mechanical
Air cleaner	Dual element
Oil Capacity	0.63 US qt (0.6l)
Fuel Tank Capacity	3.3 U.S. qts (3.1 liters)
Fuel	Unleaded 86 octane or higher
Dry Weight	35 lbs. (16.1 kg)

HONDA REPLACEMENT SPARES AVAILABLE

PTO Shaft Options	
GX200 HI QX	Parallel keyed 3/4" shaft
GX200 H1 VX1	Tapered shaft engine (Generator)
GX200OUT2 QXE4	Parallel Keyed 3/4" shaft, electric start

COMMON APPLICATIONS

- Pressure washers
- Commercial lawn and garden equipment
- Tillers / cultivators
- Generators
- Construction / industrial equipment
- Agricultural equipment
- Small vehicles
- Water pumps

GARDEN TILLER WITH HONDA GX200 ENGINE



TURFMASTER, YOUR HONDA AGENT FOR SOUTH AFRICA

*The SAE J1349 standard measures net horsepower with the manufacturer's production muffler and air cleaner in place. Net horsepower more closely correlates with the power the operator will experience when using a Honda engine powered product. The power rating of the engines indicated in this document measures the net power output at 3600 rpm (7000 rpm for model GXH50, GXV50, GX25 and GX35) and net torque at 2500 rpm, as tested on a production engine. Mass production engines may vary from this value. Actual power output for the engine installed in the final machine will vary depending on numerous factors, including the operation speed of the engine in application, environmental conditions, maintenance and other variables.

TURFMASTER

(PTY) LTD



HEAD OFFICE: NIGEL, GAUTENG

1 Third Ave, Vorsterskroon

Tel: 011 730 3400 / Fax: 011 814 2345

Email: info@turfmaster.co.za

Website: www.turfmaster.co.za

BRANCHES:

Bellville

Cnr Cilmor & Labelle Rd,
Stikland, Bellville
Tel: (021) 945-4106/7/8
Fax: (021) 946-2371

Durban

Cnr Bevis & Bishop Rd
No.11 Old Main Road, Pinetown
Tel: (031) 701 8233
Fax: (031) 701 3097

Nelspruit

Cnr Friedenheim
& Fuchsia Rd,
Nelspruit
Tel: (013) 492 0490

Port Elizabeth

20 – 6th Ave.,
Walmer, Port Elizabeth
Tel: (041) 581-8443/4/5
Fax: (041) 581-8446

Pretoria

Unit 9 Miracle Park, Lenchen Ave
Ext off Old JHB Road, Centurion
Tel: (012) 653-8342/8
Fax: (012) 653-8343

Roodepoort

9 Sonop Street,
Horizon,
Tel: 076 921 5469