

HONDA ENGINES

HONDA GXV160 VERTICAL ENGINE



Professionals rely on the GXV160 to deliver reliable, easy starting, fuel efficient performance, day in and day out.

| | |
|--------------------|--|
| Engine Type | Air-cooled 4-stroke OHV |
| Bore x Stroke | 68 X 45 mm |
| Displacement | 163 cm ³ |
| Net Power Output* | 4.3 HP (3.2 kW) @ 3,600 rpm |
| Net Torque | 7.1 lb-ft (9.6 Nm) @ 2,500 rpm |
| PTO Shaft Rotation | Counter clockwise (from PTO shaft side) |
| Compression Ratio | 8.0:1 |
| Carburetor | Float Type |
| Ignition System | Transistorized magneto |
| Starting System | Recoil |
| Lubrication System | Splash |
| Governor System | Centrifugal Mechanical |
| Air cleaner | Dual element |
| Oil Capacity | 0.69 US qt (0.65l) |
| Fuel Tank Capacity | 1.5 U.S. qts (1.4 liters) |
| Fuel | Unleaded 86 octane or higher |
| Dry Weight | 32 lb (14.5 kg) |

HONDA REPLACEMENT SPARES AVAILABLE

| PTO Shaft Options | |
|-------------------|--|
| GXV160 H2 N6 | Vertical shaft 22 mm lawnmower engine |
| GXV160 H2 MX1 | Replacement engine for HRU196 |
| GXV160 H2 MU8 | Replacement engine for HRJ216 |

COMMON APPLICATIONS

Lawn mowers
Commercial lawn and garden equipment
Forestry equipment
Construction / industrial equipment
Agricultural equipment

Three-Wheeler
with HONDA
GXV160
Engine



Turbomow 19" push mower
With HONDA GXV160 Engine



TURFMASTER, YOUR HONDA AGENT FOR SOUTH AFRICA

*The SAE J1349 standard measures net horsepower with the manufacturer's production muffler and air cleaner in place. Net horsepower more closely correlates with the power the operator will experience when using a Honda engine powered product. The power rating of the engines indicated in this document measures the net power output at 3600 rpm (7000 rpm for model GXH50, GXV50, GX25 and GX35) and net torque at 2500 rpm, as tested on a production engine. Mass production engines may vary from this value. Actual power output for the engine installed in the final machine will vary depending on numerous factors, including the operation speed of the engine in application, environmental conditions, maintenance and other variables.

TURFMASTER

(PTY) LTD



HEAD OFFICE: NIGEL, GAUTENG

1 Third Ave, Vorsterskroon

Tel: 011 730 3400 / Fax: 011 814 2345

Email: info@turfmaster.co.za

Website: www.turfmaster.co.za

BRANCHES:

Bellville

Cnr Cilmor & Labelle Rd,
Stikland, Bellville

Tel: (021) 945-4106/7/8

Fax: (021) 946-2371

Durban

Cnr Bevis & Bishop Rd
No.11 Old Main Road, Pinetown

Tel: (031) 701 8233

Fax: (031) 701 2097

Nelspruit

Cnr Friedenheim
& Fuchsia Rd,
Nelspruit

Tel: (013) 492 0490

Port Elizabeth

20 - 6th Ave.,
Walmer, Port Elizabeth

Tel: (041) 581-8443/4/5

Fax: (041) 581-8446

Pretoria

Unit 9 Miracle Park, Lenchen Ave
Ext off Old JHB Road, Centurion

Tel: (012) 653-8342/8

Fax: (012) 653 8342

Roodepoort

9 Sonop Street,
Horizon,

Tel: 076 921 5469