

KOHLER® engines

KOHLER CH440 HORIZONTAL 4-STROKE ENGINE

This gasoline engine features a 4-cycle, slant cylinder design, with a cast iron cylinder bore and overhead valve for easy access. The Quad-Clean™ 4-stage air filtration system ensures only clean air enters the engine for maximum power and life of the engine. In addition, this engine is backed by a 3 year commercial warranty.

Retail Price:
R9,115⁰⁰
INCL. VAT

From 1 – 30 April'16

Special Price:
Please
contact us



KOHLER REPLACEMENT SPARES AVAILABLE

Engine Type	4-cycle, gasoline, OHV, cast iron cylinder liners, aluminum block
J1940 Power hp(kW) ¹	14 (10.4)
Displacement cu in (cc)	24.7 (429)
Bore in (mm)	3.5 (89)
Stroke in (mm)	2.7 (69)
Peak Torque lbs. ft (Nm)	22.7 (30.8)
Compression Ratio	8.0:1
Dry Weight lbs (kg)	72.8 (33)
Oil Capacity U.S. quarts (L)	1.4 (1.3)
Lubrication	Splash
Dimensions L x W x H in	16.2 x 17.8 x 17.4
Backpressure Limit ²	40
J1995 Power hp (kW) ³	13.4 (10)

This engine powers the following equipment:



Aerator/Chipper/Shredder
Dethatcher/Edger/Logsplitter
Pressure Washer/Pump – Other
Stump Grinder/Cutter
Tiller/Aerator/Compressor
Portable Generator
Tamper
Plate Compactor

KUDU INDUSTRIAL MOWER WITH KOHLER XCH440 ENGINE

**TURFMASTER, YOUR KOHLER
AGENT FOR SOUTH AFRICA**

* Measurements are based on a recoil-start engine.

¹ Power (hp) and Torque (lbs ft) specifications for Kohler general purpose engines are rated pursuant to Society of Automotive Engineers (SAE) J1940 based on gross output testing performed according to SAE J1995 without the air cleaner and muffler. Actual engine power and torque are lower and affected by accessories (air cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed, ambient operating conditions (temperature, humidity and altitude) and other factors. This J1940 / J1995 rating provides consistent measurement to customers who may want to control the intake and exhaust features of the engine. For more information, contact Kohler Co. Engine Engineering Department. Kohler Co. reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligation.

² Inches of H₂O @ 3600 RPM WOT

³ J1995 power and torque certified by 3rd Party Witness

NOTE: Specifications may vary according to the types, and are subject to change without notice.

HEAD OFFICE: NIGEL, GAUTENG

Cnr. Third Ave & Klippen Road, Vorsterskroon

Tel: 011 730 3400 / Fax: 011 814 2345

Email: info@turfmaster.co.za

Website: www.turfmaster.co.za

TURFMASTER
BRANCHES: (PTY) LTD



Bellville
Cnr Cilmor & Labelle Rd,
Stikland, Bellville
Tel: (021) 945-4106/7/8
Fax: (021) 946-2371

Durban
Cnr Bevis & Bishop Rd
No.11 Old Main Road, Pinetown
Tel: (031) 701 8233
Fax: (031) 701 3097

Port Elizabeth
20 – 6th Ave.,
Walmer, Port Elizabeth
Tel: (041) 581-8443/4/5
Fax: (041) 581-8446

Pretoria
Unit 9 Miracle Park, Lenchen Ave Ext off
Old JHB Road, Centurion
Tel: (012) 653-8342/8
Fax: (012) 653-8343

KOHLER® engines



KOHLER DEALERS:

PROVINCE	TOWN	NAME	TEL NUMBER	EMAIL ADDRESS
GAUTENG	NIGEL	Turfmaster Head Office	011 730 3400	info@turfmaster.co.za
	PRETORIA	Dennis Mowers	012 653 8342/8	dennismow@mweb.co.za
EASTERN CAPE	PORT ELIZABETH	Turfmaster Port Elizabeth Magnacorp 175 cc	041 581 8443/4/5	marius@turfmaster.co.za
KWAZULU-NATAL	PINETOWN	Turfmaster Durban	031 701 8233	tmaster@dbn.stormnet.co.za
WESTERN CAPE	BELLVILLE	Turfmaster Bellville Magnacorp 174 cc	021 945 4106/7/8	morne@turfmaster.co.za richard@turfmaster.co.za