

KOHLER® engines

KOHLER XT775 VERTICAL 4-STROKE ENGINE

The KOHLER XT Series™ engines features professional-grade features like Overhead Valve (OHV) design for fuel efficiency and cast iron cylinder liners for durability. User-friendly features like Accu-Fill® and Easy-Pull technology make it easy for the homeowner to operate. It is EPA emissions-compliant and is backed by a two-year warranty. Four-cycle, single-cylinder, air-cooled, vertical shaft, gasoline, OHV, with cast iron liner.



Engine Type	Four-cycle, single-cylinder, air-cooled, vertical shaft, gasoline, OHV, with cast iron liner.
J1940 Torque lbs. ft (Nm) ¹	7.75 (10.5)
Displacement cu in (cc)	10.6 (173)
Bore in (mm)	2.7 (70)
Stroke in (mm)	1.8 (45)
Compression Ratio	8.5:1
Dry Weight lbs (kg)	26.9 (12.2)
Oil Capacity U.S. quarts (L)	0.625 (0.59)
Lubrication	Splash
Dimensions L x W x H in	17.1 x 13.9 x 11
Backpressure Limit ²	40
J1995 Torque lbs ft (Nm) ³	7.46 (10.11)
J1995 Rated Speed (RPM)	2800

KOHLER REPLACEMENT SPARES AVAILABLE



This engine powers the following equipment:

- Walk Mower
- Aerator/ Chipper/Shredder
- Dethatcher/Edger
- Logsplitter/Pressure Washer
- Pump - Other
- Stump Grinder/Cutter
- Tiller/Compressor
- Ice Drill/Portable Generator
- Pressure Washer
- Tamper/Plate Compactor

TURBOMOW PUSH MOWER WITH KOHLER XT8 ENGINE

TURFMASTER, YOUR KOHLER AGENT FOR SOUTH AFRICA

* Length is front of blower housing to back of blower housing. Width is air cleaner to muffler. Height is mounting surface to grass screen.

¹ Power (hp) and Torque (lbs ft) specifications for Kohler general purpose engines are rated pursuant to Society of Automotive Engineers (SAE) J1940 based on gross output testing performed according to SAE J1995 without the air cleaner and muffler. Actual engine power and torque are lower and affected by accessories (air cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed, ambient operating conditions (temperature, humidity and altitude) and other factors. This J1940 / J1995 rating provides consistent measurement to customers who may want to control the intake and exhaust features of the engine. For more information, contact Kohler Co. Engine Engineering Department. Kohler Co. reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligation.

² Inches of H₂O @ 3600 RPM WOT

³ J1995 power and torque certified by 3rd Party Witness

NOTE: Specifications may vary according to the types, and are subject to change without notice.

TURFMASTER (PTY) LTD



BRANCHES:

Bellville
Cnr Cilmor & Labelle Rd,
Stikland, Bellville
Tel: (021) 945-4106/7/8
Fax: (021) 946-2371

Durban
Cnr Bevis & Bishop Rd
No.11 Old Main Road, Pinetown
Tel: (031) 701 8233
Fax: (031) 701 3097

Port Elizabeth
20 – 6th Ave.,
Walmer, Port Elizabeth
Tel: (041) 581-8443/4/5
Fax: (041) 581-8446

Pretoria
Unit 9 Miracle Park, Lenchen Ave Ext off
Old JHB Road, Centurion
Tel: (012) 653-8342/8
Fax: (012) 653-8343

HEAD OFFICE: NIGEL, GAUTENG
Cnr. Third Ave & Klippen Road, Vorsterskroon
Tel: 011 730 3400 / Fax: 011 814 2345
Email: info@turfmaster.co.za
Website: www.turfmaster.co.za

KOHLER[®] engines

TURFMASTER 
(PTY) LTD

KOHLER DEALERS:

PROVINCE	TOWN	NAME	TEL NUMBER	EMAIL ADDRESS
GAUTENG	NIGEL	Turfmaster Head Office	011 730 3400	info@turfmaster.co.za
	PRETORIA	Dennis Mowers	012 653 8342/8	dennismow@mweb.co.za
EASTERN CAPE	PORT ELIZABETH	Turfmaster Port Elizabeth Magnacorp 175 cc	041 581 8443/4/5	marius@turfmaster.co.za
KWAZULU-NATAL	PINETOWN	Turfmaster Durban	031 701 8233	tmaster@dbn.stormnet.co.za
WESTERN CAPE	BELLVILLE	Turfmaster Bellville Magnacorp 174 cc	021 945 4106/7/8	morne@turfmaster.co.za richard@turfmaster.co.za